

MENU

SEARCH

INDEX

DETAIL

1/1



JAPANESE PATENT OFFICE

PATENT ABSTRACTS OF JAPAN

(11)Publication number: 11017596

(43)Date of publication of application: 22.01.1999

(51)Int.Cl.

H04B 7/08

(21)Application number: 09163053

(71)Applicant:

NEC CORP

(22)Date of filing: 19.06.1997

(72)Inventor:


ATSUTA HIROSADA

(54) IN-PHASE COMBINATION SPACE DIVERSITY RECEIVER

(57)Abstract:

PROBLEM TO BE SOLVED: To avoid effect at an inverse phase point of a dead band provided to improve noise improvement and improve a control speed for in-phase combination control in the in-phase combination space diversity receiver where a lead/ lag is discriminated based on a phase difference of two reception input signals so as to control the phase difference when both input signals are put together.

SOLUTION: When a phase relation of two reception input signals S1, S2 is discriminated to be in an inverted phase range ($90^\circ < \Delta\theta < 270^\circ$) by a 2nd phase difference discrimination means 24, a phase shift amount control means 25 receiving the discrimination signal controls a phase shift means 21 to change the phase shift amount of the phase shift means by 180° at that point of time. The phase control based on the discrimination result of the 1st phase difference discrimination means 23 is conducted always within an in-phase range ($-90^\circ < \Delta\theta < 90^\circ$), the effect of a dead band in an inverse phase point is not received and even in the case of phase control near an inverted phase with a high phase difference is converted to the in phase point at a high speed.



LEGAL STATUS